VP-100i

Integrated Amplifier

All Vacuum Tube Design – All Hand Made

System	Vacuum Tube Integrated Amplifier
Frequency Response	10Hz – 45kHz ± 1.5dB
THD	1% [1kHz]
S/N Ratio	91dB
Input Impedance	> 100K Ohm (RCA)
Tubes	KT88 × 4, 6SN7 × 3, 6SL7 × 2
Dimensions	440 × 388 × 207mm [W×H×D]
Weight	30.5kg
Accessories	Remote Control
Input Terminals	Aux, Tuner, CD
Output Terminals	Tape Out
Circuit	Switchable Triode/Ultralinear

Finish	Chassis Black, Transformer Black Paint
Front Finish	Silver
Sensitivity	400mV, 600mV (Pre in)
Output Impedance	4 Ohm, 8 Ohm
Power Output	2 × 24w (8 Ohm, Triode), 2 × 50w (8 Ohm Ultralinear)
Consumption	Max. 270w

Distributed in Australia and New Zealand by:

Final Link Audio Pty Ltd
Distributors of Quality Audio Products

Final Link Audio Pty Ltd
Phone +61 3 9746 0394
Facsimile +61 3 9747 3063
Email info@finallink.com.au
Internet www.finallink.com.au

Pictures shown are for illustration purposes only. Specifications may change without notice. Information quoted in this catalogue is correct at the time of printing. However as part of our on going research and development programs improvements and small specification changes may result.

Authorised Dealer:

Artwork by zanatta.com.au