



Internal View

### Pure Class A Design – All Hand Made

System	Pure Class A Integrated Amplifier
Power Output	2 × 40w (8 Ohm)
Frequency Response	20Hz – 40kHz
THD	0.12% (1kHz)
S/N Ratio	92dB
Input Impedance	100K Ohms
Input Sensitivity	500mV
Power Consumption	200w
Weight	23kg
Internal Construction	Hand made, short signal path
Chassis	Heavy gauge thick aluminium, heavy heat sinks
Output Transformers	Custom made low Imp/wide bandwidth
Power Supply	Custom made Toroidal

Protection	Thermal overload protection
Terminals	WBT style speaker/gold plated RCA ×5, XLR balanced
Capacitors	Realcap/Nichicon
Remote Control	Full function aluminium
Finish	Silver

**Distributed in Australia  
and New Zealand by:**



Distributors of Quality Audio Products

Final Link Audio Pty Ltd  
Phone +61 3 9746 0394  
Facsimile +61 3 9747 3063  
Email [info@finallink.com.au](mailto:info@finallink.com.au)  
Internet [www.finallink.com.au](http://www.finallink.com.au)

Pictures shown are for illustration purposes only.  
Specifications may change without notice. Information  
quoted in this catalogue is correct at the time of  
printing. However as part of our on going research  
and development programs improvements and small  
specification changes may result.

**Authorised Dealer:**

