

H-80A

Hybrid Class-A Integrated Amplifier



Internal View



Hybrid Class A Design – All Hand Made

System	Dual Mono, Hybrid Class A Integrated Amplifier
Terminals	WBT Style Speaker / Gold Plated RCA × 5 Tape Out × 1 Balanced XLR × 1
Power Output	80w + 80w (8 Ohm) Class A type 150w + 150w (4 Ohm) Class A/B type
Remote Control	Full function
Pre-Amplifier Tube Compliment	2 × 12AU7 Input Tube
Frequency Response	10Hz – 40kHz
THD	<0.2% 1kHz, 80w (8 Ohm)
S/N Ratio	91dB
Input Sensitivity	380mV
Input Impedance	100k Ohm (RCA)

Power Consumption	280w
Weight	35kg
Dimensions	440 × 235 × 533 mm [W×H×D]
Other	Dual 450w power transformers, extra large cooling radiator, black acrylic decorated panel, heavy duty knockdown adjustable amp feet, each foot can adjust the height independently, index type peak VU value ampere meter with blue background light.

**Distributed in Australia
and New Zealand by:**



Distributors of Quality Audio Products

Final Link Audio Pty Ltd
Phone +61 3 9746 0394
Facsimile +61 3 9747 3063
Email info@finallink.com.au
Internet www.finallink.com.au

Pictures shown are for illustration purposes only.
Specifications may change without notice. Information
quoted in this catalogue is correct at the time of
printing. However as part of our on going research
and development programs improvements and small
specification changes may result.

Authorised Dealer:

